



EIB ASCII Terminal

Accessing the EIB/KNX using an easy ASCII protocol by the RS-232 interface



Highlights

- Easiest access to the EIB/KNX
- Standard ASCII-Code
- Supports all group addresses simultaneously
- Supports all non-structured EIS-types
- Simple setup using a terminal program
- Built in german and english help texts
- Fully transparent even at 100% bus load
- Built in filter- and EIS-type tables
- All values read- and writeable using plain text
- Simple integration of the EIB/KNX into own systems (PC, Microcontroller, Linux,...)
- Built in bus coupling unit
- Standard RS-232 Interface, no system drivers required
- Small housing (67*92*26mm)

Fields of application

If you simply need to write values to certain addresses of your EIB/KNX, or you want to know the current value of addresses, you do not need to use a complex protocol any more. You just send easy ASCII commands to the EIB ASCII Terminal. To write the value "1" to the group address "1/2/3" you have to send the ASCII text sequence "W1/2/3=1". That's all you have to do! Therefore you can easily connect your own applications and systems to the EIB/KNX world without MS Windows, you just have to be able to handle a RS-232 interface.

Contents of delivery

- EIB ASCII Terminal
- Cable set
- Parametrization software b+b Terminal
- Documentation

b+b Automations- und Steuerungstechnik GmbH

Beerfelden Site I · Dieselstraße 18 · Airlenbach Site II · Eichenstraße 38a · 64760 Oberzent (Germany)

phone: +49 (0) 6068 9310-0 · fax: +49 (0) 6068 9310-99

info@bb-automation.com · www.bb-automation.com

